



NOTE:
FOR DRAINAGE APPLICATIONS ONLY

1. FVMS-01 wall mounting kit, sold separately.
2. Working pressure of 10.75 PSI.
3. Cracking head 0.4 PSI
4. Exceeds the leakage rate and manufacturing requirements as per BS 7775 and DIN 19569-4 for a Class 5 valve.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.	TOLERANCES: FRACTIONAL $\pm 1/4"$.XX = $\pm .06$ ANG. = $+3^\circ$ UNLESS OTHERWISE SPECIFIED	GASKET	EPDM RUBBER	CONFORMS TO: BS 7775 DIN 19569-4	PART WEIGHT: 9.7 LBS	AUTHOR: TYLER KELLER	DATE: 3/11/2026	SCALE: NOT TO SCALE
		BODY	HMPE					
		STEEL COMPONENTS	316SS					
					REVISION: A	CHECKER:	UNITS: INCHES	SHEET: 1 OF 1