



PipePatch[®]

NO DIG

PIPE REPAIR SYSTEM



ECO
FRIENDLY
CONTAINS NO VOCs

PIPEPATCH[®] CERTIFICATIONS &

STANDARDS COMPLIANCE



Plastic Piping System
Components and Related
Materials



IAPMO Research and Testing
assessment of the Quality
Assurance System



PipePatch complies with standards ASTM F 1216/
ASTM F 3541 "Standard Practice for Rehabilitation
of Existing Pipelines and Conduits by Inversion and
Curing of a Resin-Impregnated Tube"

PIPEPATCH® STANDARD

| | Part Number | Description | Part Number | Description |
|------------|-------------|-------------------------|-------------|-------------------------|
| 24" LENGTH | FPP-3 | 3" x 24" PipePatch Kit | FPP-3X48 | 3" x 48" PipePatch Kit |
| | FPP-4 | 4" x 24" PipePatch Kit | FPP-4X48 | 4" x 48" PipePatch Kit |
| | FPP-6 | 6" x 24" PipePatch Kit | FPP-6X48 | 6" x 48" PipePatch Kit |
| | FPP-8 | 8" x 24" PipePatch Kit | FPP-8X48 | 8" x 48" PipePatch Kit |
| | FPP-10 | 10" x 24" PipePatch Kit | FPP-10X48 | 10" x 48" PipePatch Kit |
| | FPP-12 | 12" x 24" PipePatch Kit | FPP-12X48 | 12" x 48" PipePatch Kit |
| | FPP-15 | 15" x 24" PipePatch Kit | FPP-15X48 | 15" x 48" PipePatch Kit |
| | FPP-18 | 18" x 24" PipePatch Kit | FPP-18X48 | 18" x 48" PipePatch Kit |
| | FPP-24 | 24" x 24" PipePatch Kit | FPP-24X48 | 24" x 48" PipePatch Kit |
| 48" LENGTH | | | | |

PIPEPATCH® ELBOW

| | Part Number | Description | Part Number | Description |
|-----------|-------------|------------------------------|-------------|------------------------------|
| 24" ELBOW | FPP-EL2 | 2" x 18" Elbow PipePatch Kit | FPP-EL3X48 | 3" x 48" Elbow PipePatch Kit |
| | FPP-EL3 | 3" Elbow PipePatch Kit | FPP-EL4X48 | 4" x 48" Elbow PipePatch Kit |
| | FPP-EL4 | 4" Elbow PipePatch Kit | | |
| | FPP-EL6 | 6" Elbow PipePatch Kit | FPP-EL6X48 | 6" x 48" Elbow PipePatch Kit |
| | FPP-EL8 | 8" Elbow PipePatch Kit | | |
| | FPP-EL10 | 10" Elbow PipePatch Kit | | |
| 48" ELBOW | | | | |

PIPEPATCH® XTEND

| Part Number | Description |
|---------------|--|
| FPP-EXT-3x120 | 3" x 120" Pipe XTEND Pull-in-Place kit |
| FPP-EXT-3x180 | 3" x 180" Pipe XTEND Pull-in-Place kit |
| FPP-EXT-4x120 | 4" x 120" Pipe XTEND Pull-in-Place kit |
| FPP-EXT-4x180 | 4" x 180" Pipe XTEND Pull-in-Place kit |
| FPP-EXT-6x120 | 6" x 120" Pipe XTEND Pull-in-Place kit |
| FPP-EXT-6x180 | 6" x 180" Pipe XTEND Pull-in-Place kit |
| FPP-EXT-8x120 | 8" x 120" Pipe XTEND Pull-in-Place kit |
| FPP-EXT-8x180 | 8" x 180" Pipe XTEND Pull-in-Place kit |

PIPEPATCH® PILLOW

| Part Number | Description |
|-------------|----------------------------------|
| FPP-3036x48 | 30" to 36" x 48" Kit No Fold Kit |
| FPP-4248X48 | 42" to 48" x 48" Kit No Fold Kit |
| FPP-60X48 | 60" x 48" No Fold Kit |
| FPP-72X48 | 72" x 48" No Fold Kit |



SCAN HERE
TO VIEW OUR FULL LINEUP
OF PIPEPATCH KITS, EQUIPMENT AND ACCESSORIES



X-SEAL

Hydrophobic polyurethane sealant that bonds to concrete, metal, plastic, wood, and pre-cast connections to prevent infiltration.

SEALGUARD II

Polyurethane grout that quickly seals active leaks in precast, cement, or brick structures, stopping infiltration permanently.

QSR

Rapid-setting, acid-resistant calcium aluminate for bench, invert, and void rehab. Sets in 10-15 minutes for quick restoration.

HYPERFLEX

Hydrophobic polyurethane grout that seals concrete leaks with a permanent, non-shrinking bond. NSF-ANSI-CAN 61 approved for potable water.

STRONG PLUG

Rapid-setting (60 seconds), hand-applied cementitious product for stopping infiltrating water.

MS-2®A | MS-2®C

MS-2A is cost-effective for infiltration and structural restoration, while **MS-2C** offers high early strength and corrosion resistance in mild sulfide environments.

HIGH PERFORMANCE

100% calcium aluminate mortar that restores structures in corrosive environments, stopping infiltration and forming a durable liner for pH 1.0+ substrates.



STRONG COMPANY

CEMENTITIOUS REPAIR PRODUCTS

• COMPREHENSIVE REHABILITATION

Strong-Seal® Systems are engineered to restore concrete and masonry structures, addressing inflow, infiltration, and corrosion.

• MANHOLE SOLUTIONS

Specialized cementitious products and patented equipment designed for effective manhole rehabilitation.

• STORMWATER REPAIR

Storm Seal® restores pipes, culverts, and basins using cost-effective centrifugal casting or spraying methods.



Part Number

Description

| | |
|----------------------|---|
| GROUT250 | Strong-Seal Grout 250 Cementitious Grout Void and Leak Stabilization 60 lb. Bag |
| GROUT1000 | Strong-Seal Grout 1000 High-Strength Cementitious Grout 60 lb. Bag |
| GROUT12000 | Strong-Seal Grout 12000 Self-Consolidating Grout 65 lb. Bag |
| STORM-SEAL | Strong-Seal® Storm Seal® Spray-Applied Lining 60 lb. Bag |
| QSR-PAIL | Strong-Seal® QSR Fast-Acting Repair Mortar 40 lb. Bucket |
| QSR-BAG | Strong-Seal® QSR Fast-Acting Repair Mortar 50 lb. Bag |
| PROFILE-PLUS | Strong-Seal Profile Plus Cementitious Liner 60 lb. Bag |
| STRONG-PLUG | Storm-Seal® Strong-Plug® Rapid-Acting Leak-Stop Cement 50 lb. Bucket |
| MS-2C | Strong-Seal MS-2®C Bag High-Strength Mortar 60 lb. Bag |
| MS-2A | Strong-Seal MS-2®A Economical Cementitious Mortar 60 lb. Bag |
| HIGH-PERFORMANCE-MIX | Strong-Seal High Performance Mix 60 lb. Bag |
| GEOPOLYMER | Strong-Seal Geopolymer for Structural Rehabilitation 65 lb. Bag |

SealGuard^{inc}

WORLD CLASS WATER SEALING SOLUTIONS



SEALGUARD

HYDROPHOBIC POLYURETHANE GROUT REPAIR PRODUCTS

| Part Number | Description |
|--------------|--|
| SG-6KITST | SealGuard II Starter Kit (6pk) with Dual Component Caulk Gun |
| SG-CGUND | Premium Dual Component Caulk Gun |
| SG-CGUNPN | Pneumatic Dual Component Caulk Gun |
| SG-MXP6 | SealGuard II Static Mixers (6 pk) |
| SG-MXP12 | SealGuard II Static Mixers (12 pk) |
| SG-RE6 | SealGuard II Reorder Kit (6 pk) with mixing tips |
| SG-RE12 | SealGuard II Reorder Kit (12 pk) with mixing tips |
| SG-HF6 | HyperFlex (300 mil cart.) 6 pack |
| SG-HF12 | HyperFlex (300 mil cart.) 12 pack |
| SG-HF12TIP | HyperFlex Tips (12 pk) |
| SG-HF5G | HyperFlex (5 gallon container) |
| SG-X-SEAL-12 | X- Seal (12-300 ml Kit) |



• RAPID REACTION TIME

SealGuard II is a dual-component hydrophobic polyurethane that reacts within 1 to 3 seconds, effectively stopping high-flow leaks exceeding 50 gallons per minute.

• DURABLE AND NON-SHRINKING

Being hydrophobic, SealGuard grouts do not absorb water or shrink after curing, ensuring long-lasting seals in various structures, including manholes, vaults, and tunnels.

• VERSATILE APPLICATION

Suitable for both high-flow and low-flow leaks, SealGuard products can be injected into fine fractures and perform well even in the presence of flowing water, making them ideal for diverse infrastructure repairs.

