



NOTE:

FOR DRAINAGE APPLICATIONS ONLY

1. FVMS-04 wall mounting kit, sold separately.
2. Working pressure of 10.75 PSI.
3. Cracking head 0.4 PSI
4. Exceeds the leakage rate and manufacturing requirements as per BS 7775 and DIN 19569-4 for a Class 5 valve.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.

TOLERANCES:
FRACTIONAL ± 1/4"
.XX = ± .06
ANG. = +3°
UNLESS OTHERWISE SPECIFIED

GASKET	EPDM RUBBER
BODY	HMWPE
STEEL COMPONENTS	316SS

MANUFACTURED TO:	BS 7775 DIN 19569-4
PART WEIGHT:	28.7 LBS
REVISION:	A

AUTHOR:	TYLER KELLER
CHECKER:	

DATE:	5/21/2026
UNITS:	INCHES

SCALE:	NOT TO SCALE
SHEET:	1 OF 1