



**NOTE:**  
**FOR DRAINAGE APPLICATIONS ONLY**

1. FVMS-01 wall mounting kit, sold seperately.
2. Working pressure of 10.75 PSI.
3. Cracking head 0.4 PSI
4. Exceeds the leakage rate and manufacturing requirements as per BS 7775 and DIN 19569-4 for a Class 5 valve.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.	<b>TOLERANCES:</b> FRACTIONAL $\pm 1/4"$ .XX = $\pm .06$ ANG. = $+3^\circ$ UNLESS OTHERWISE SPECIFIED	GASKET	EPDM RUBBER	CONFORMS TO:	PART WEIGHT:	AUTHOR:	DATE:	SCALE:
		BODY	HMPE	BS 7775	6.4 LBS	TYLER KELLER	3/11/2026	NOT TO SCALE
		STEEL COMPONENTS	316SS	DIN 19569-4	REVISION:	CHECKER:	UNITS:	SHEET: 1 OF 1
					A		INCHES	