



On Demand Flood Protection **When Every Second Counts**

Installation Instructions

Step 1: Position the Bags

Place StormStop Sandless Sandbags in the area you want to protect before flooding or water intrusion occurs. **Common applications include doorways, garages, basements, driveways, and low-lying areas prone to flooding.**

Step 2: Activate with Fresh Water

Thoroughly saturate each bag with fresh water using a garden hose, bucket, or other freshwater source. **Allow approximately 10 minutes for the bags to fully expand.**

*Note: StormStop is designed for use with fresh water only. **Do not activate with salt water.***

Step 3: Build Your Barrier

Place activated bags tightly together to create a continuous barrier. **For water levels exceeding 3.5", stack bags in a staggered brick pattern.**

Step 4: Stack Properly

- Use a 1:3 stacking ratio
- For every 1 ft. of wall height, create a 3 ft. wide base
- Always build the barrier higher than the anticipated water level

Step 5: Monitor During Use

Check the barrier periodically and **reposition bags if necessary** to maintain protection.

Important Information

- **Indoor & Outdoor Use**
- White crystals or gel near seams during first activation are normal and harmless.
- Properly activated bags are designed to stay in place.
- Store unused bags in a cool, dry location. **Shelf life: 10+ years when kept dry.**
- Dispose of used bags according to local regulations.

Warnings

- **Fresh water activation only.**
- Do not use with salt water, chlorine, lime, or calcium solutions.
- Wet surfaces may become slippery.
- **Do not cut or puncture bags.**
- Some seepage may occur on uneven or porous surfaces.